

AIR BAG SYSTEM

BACKGROUND OF THE INVENTION

Do
Not
Enter
EC
1/2/103
Enter
Claims
and
abstract
only
EC
1/2/103

5 The present invention relates to an air bag system housed in an instrument panel in front of a front occupant seat of a vehicle. More particularly, the present invention relates to an air bag system dealing with air bags of which various sizes are required for different car types corresponding to a constant output of an inflator.

10 DESCRIPTION OF THE RELATED ART

The air bag system is housed in a housing portion in a front instrument panel. The air bag is housed in a folding state in a retainer of the air bag system. High-pressure gas generated from an inflator is introduced into the air bag at the time of a collision of a vehicle, so that the air bag is inflated toward a front seat occupant for restraining the forward movement of the occupant due to inertia force.

In air bag systems, different sizes of air bags are required to be housed corresponding to different car types which individually require different restraining performances. It is true in the current situation that there is a big difference in sizes between car types.

Since an air bag is inflated with high-pressure gas generated from an inflator (a gas generating device), the

25

sizes of the air bag are one of the factors to determine the output of the inflator. As the sizes of the air bag are expanded, the volume thereof is increased. The increasing volume leads to a requirement of an inflator having a higher output.

5 As a result, inflators having different outputs need to be prepared for air bags of different sizes and volumes, and therefore the compatibility of air bag systems of the related art among car types remains low.

10 SUMMARY OF THE INVENTION

It is an object of the present invention to provide an air bag system which can properly use various sizes of air bags corresponding to a constant output of a given size inflator, which are required for different car types.

15 In view of the aforesaid problem, after earnest studies the inventors have come to a conclusion that the problem may be solved by an air bag system including an air bag in a folded state housed in an instrumental panel, the air bag inflates by an inflator when a vehicle is crashed, wherein the air bag comprises:

an opening portion into which a gas generated by the inflator flows;

a gas flow path portion; and

25 an occupant restraint portion, wherein

the gas flows from the opening portion to the occupant restraint portion through the gas flow path portion.

Namely, the air bag system according to the present invention is characterized by providing at least one
5 penetrating portion in the air bag.

In addition, the air bag system according to the invention is characterized by provision of at least one joint portion in the air bag.

Furthermore, it is possible to provide both the
10 penetrating portion(s) and the joint portion(s) in the air bag.

It is preferable to provide the penetrating portion and/or the joint portion in the gas flow path portion of the air bag to divide the gas flow portion into multiple gas flow
15 paths. This allows only the volume of the gas flow path portion to be adjusted, while keeping restraining performance of the air bag.

The penetrating portion and/or the joint portion may be provided between the opening portion and the gas flow path
20 portion of the air bag, whereby the gas flow path portion may be divided into multiple gas flow paths.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a cross-sectional view of an instrument panel
25 portion where an air bag according to the invention is housed;

Fig. 2 is a perspective view showing an air bag according to one embodiment of the present invention;

Fig. 3 is a cross-sectional view of the air bag taken
5 along the line A-A thereof in Fig. 2;

Fig. 4 is a perspective view showing an air bag according to another embodiment of the present invention;

Fig. 5 is a cross-sectional view of the air bag taken along the line B-B in Fig. 4;

10 Fig. 6 is a perspective view showing a production process of the air bag shown in Fig. 4;

Fig. 7 is a perspective view showing an air bag according to a further embodiment of the present invention;

Fig. 8 is a cross-sectional view of the air bag taken
15 along the line C-C thereof in Fig. 7;

Fig. 9 is a perspective view showing an air bag according to an embodiment of the present invention.

Fig. 10 is a cross-sectional view of the air bag taken along the line D-D thereof in Fig. 9;

20 Fig. 11 is a perspective view showing an air bag according to another embodiment of the present invention;

Fig. 12 is a cross-sectional view of the air bag taken along the line E-E thereof in Fig. 11;

Fig. 13 is a perspective view showing an air bag according
25 to a further embodiment of the present invention;

Fig. 14 is a perspective view showing an air bag according to a further embodiment of the present invention;

Fig. 15 is a cross-sectional view of the air bag taken along the line F-F thereof in Fig. 14;

5 Figs. 16(a) and 16(b) are cross-sectional views similar to Fig. 15 showing a modification of the air bag in Fig. 14, in which Fig. 16(a) shows the air bag in a folded up state and Fig. 16(b) shows the air bag in an inflated state;

Fig. 17 is a perspective view showing an air bag according to another embodiment of the present invention;

Fig. 18 is a cross-sectional view of the air bag taken along the line G-G thereof in Fig. 17;

Fig. 19 is a perspective view showing an air bag according to a further embodiment of the present invention;

15 Fig. 20 is a cross-sectional view of the air bag taken along the line H-H thereof in Fig. 19;

Fig. 21 is a perspective view of the air bag according to a further embodiment of the present invention;

Fig. 22 is a cross-sectional view of the air bag taken along the line I-I thereof in Fig. 21; and

Fig. 23 is a cross-sectional view of the air bag taken along the line J-J thereof in Fig. 21.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

25 Fig. 1 is a cross-sectional view showing the deployed

state of an air bag of one embodiment of an air bag system according to the present invention.

As shown in Fig. 1, the air bag system 1 is preferably housed at an upper portion in an instrument panel 11. The
5 air bag system 1 comprises:

an airtight container-like retainer 12 which opens to an upper surface of the instrument panel 11; and
lids 13a and 13b which close an upper end opening of the retainer 12.

10 An inflator 14 and an air bag 15 are accommodated in the interior of the retainer 12. The interior of the retainer has an air bag housing portion. The inflator 14 is a container including a gas generating agent such as pyrotechnic material. When a collision is detected through deceleration of a vehicle,
15 the gas generating agent is ignited and high-pressure gas is then gushed or rapidly expelled out. The air bag 15 is something like a bag which opens at one end thereof. The air bag 15 is joined airtight at the opening portion thereof to the retainer in such a manner that a gas generated from the
20 inflator 14 flows in the air bag 15.

When the speed of the vehicle is drastically reduced due to a collision or the like, an acceleration sensor detects the deceleration of the vehicle to ignite the gas generating agent in the inflator 14. Then, high-pressure gas is gushed
25 out and the air bag 15 is pressed against lower surfaces of

the lids 13a and 13b. As a result, the lids 13a and 13b are then pushed up to rotate upwardly to thereby open the upper end opening of the retainer 12. Therefore, the air bag 15 is inflated through the opening.

5 The air bag 15 comprises the opening portion, a gas flow path portion 16 and an occupant restraint portion 17. The gas flow path portion 16 is a portion which substantially covers an upper surface of the instrument panel when the air bag is inflated.

10 The gas flowing out of the inflator 14 passes through the gas flow path portion 16 of the air bag via a gas flow-in portion in the retainer 12 and flows into the occupant restraint portion 17.

15 The air bag 15 is made of an airtight and soft material such as a nylon woven fabric and is preferably formed into a bag-like configuration using polyamide threads. In addition, it is preferable to have rubber or silicone having heat resistance coated on an internal surface of the air bag 15.

20 According to the air bag system of the present invention, the volume of air bags may be maintained constant by providing a penetrating portion or portions and/or a joint portion or portions in predetermined sizes in the air bag. Due to this, the same size inflator may be used on different car types while maintaining the occupant restraining performance of
25 the air bag.

It is preferable to provide the penetrating portion or portions and/or the joint portion or portions in the above gas flow path portion, whereby only the volume of the gas flow portion is adjusted and the maintenance of the occupant
5 restraining performance can be eased.

An example will be described in which the gas flow path portion is penetrating partially into at least one of the flow paths by providing the penetrating portion in the gas flow path portion.

10 Fig. 2 is a perspective view showing a completely inflating state of an air bag having a penetrating portion. Fig. 3 is a cross-sectional view of the air bag taken along the line A-A in Fig. 2.

20 The penetrating portion 21 may be formed, whereby a panel 22 joins an opening hole in an upper panel of the gas flow path portion with a hole in a lower panel thereof. The panel 22 is a separate component extending along ports of the holes for the penetrating portion. The joining of the panel 22 can be implemented using a suturing method, a thermal fusing method or a bonding method using an adhesive (reference numerals 23 and 24 denoting sutured portions).

25 The gas generated from the inflator passes through an opening 25, then flows into flow paths 26a and 26b which are situated on sides of the penetrating portion 21 in the gas flow path portion, and finally flows into the occupant restraint

portion.

Furthermore, preferably vent holes are provided in an air bag for exhausting the gas.

In the air bag 2, as shown in Fig. 2, vent holes 27a
5 and 27b are provided in both side panels thereof.

Fig. 4 is a perspective view showing a completely deployed
state of an air bag 3 with a penetrating portion according
to another example, and Fig. 5 is a cross-sectional view of
the air bag 3 taken along the line B-B in Fig. 4. In addition,
10 Fig. 6 is a perspective view showing one process for producing
the air bag 3. A penetrating portion 31 can be formed by
joining parts of upper and lower panels of a gas flow path
portion in an oval fashion through suturing and then cutting
out a joint portion 33 inside a sutured portion 32. Preferably
15 polyamide threads are used for suturing. The gas generated
from the inflator flows into flow paths 34a and 34b, which
are situated on both sides of the penetrating portion in the
gas flow path portion, and finally the gas flows into a occupant
restraint portion of the air bag.

20 While there is no limitation to the configuration of
the penetrating portion, a circular, oval, square or diamond
shape may be preferred since the shapes can facilitate the
formation of the penetrating portion.

In addition, the penetrating portion may be provided
25 in an end portion of the gas flow path portion attached to

the opening of the air bag. Fig. 7 is a perspective view showing a completely inflating state of an air bag according to an example of the invention in which a penetrating portion is provided at an end portion of the gas flow path portion 5 attached to the opening of the air bag. Fig. 8 is a cross-sectional view of the air bag 4 taken along the line c-c thereof in Fig. 7. In this case, the openings 45a and 45b of the air bag 4 are formed as a penetrating configuration. The gas passes through the openings 45a and 45b and flows into an 10 occupant restraint portion via flow path portions 46a and 46b.

Fig. 9 is a perspective view showing the completely inflating state of an air bag according to another example of the invention in which a penetrating portion is provided 15 at the end portion of the opening portion. Fig. 10 is a cross-sectional view of the air bag shown in Fig. 9 taken along the line D-D thereof. In this case, the openings 53a and 53b of the air bag are formed into a penetrating configuration. The gas passes through the openings 53a and 53b and flows 20 into an occupant restraint portion via the flow paths 54a and 54b.

A plurality of penetrating portions may be provided in the gas flow path portion using a method similar to those described heretofore. Fig. 11 is a perspective view showing 25 a completely inflating state of an air bag of an example in

which a plurality of penetrating portions are provided in a gas flow path portion. Fig. 12 is a cross-sectional view of the air bag 6 shown in Fig. 11 taken along the line E-E. The gas flows from a gas flow path portion into flow paths
5 situated on sides of a penetrating portion 61a. The flow path portion is further penetrated at penetrating portions 61b and 61c into flow paths 63a, 63b and 63c and finally flows into the occupant restraint portion.

Additionally, while the penetrating portion preferably
10 pierces the gas flow path portion vertically, the penetrating portion may pierce the gas flow path portion transversely or a combination those vertical and transverse penetrating portions may be adopted.

Fig. 13 is a perspective view showing a completely
15 inflating state of an air bag according to a further example of the invention in which penetrating portions are provided in such a manner as to pierce a gas flow path portion vertically and transversely. The penetrating portions of the air bag 7 can be formed by providing notches for vertical penetrating
20 portions in upper and lower panels of the gas flow path portion from openings and suturing a panel 71 which is a separate component (and is provided with notches for transverse penetrating portions) along the notches as shown in Fig. 13 (reference numerals 72, 73, 74 and 75 denoting sutured portions).
25 The opening of the air bag 7 penetrates into four openings.

However, in case the penetrating portions are provided in such a manner as to start from openings of an air bag, the number and configuration of gas flow-in portions within a retainer should be made to coincide with those of the openings of the air bag.

Fig. 14 is a perspective view showing a completely deployed state of an air bag according to an example of the invention in which joint portions are provided, and Fig. 15 is a cross-sectional view of the air bag 8 shown in Fig. 14 taken long the line F-F thereof. Joint portions 81 and 82 are formed by linearly joining parts of upper and lower panels together at two locations in an air bag deployment direction. A suturing method, a thermal fusing method or a bonding method using an adhesive may be used as a method for joining the upper panel to the lower panel (reference numerals 81 and 82 denoting sutured or joint portions).

Figs. 16(a) and 16(b) are cross-sectional views showing the cross section taken along the line F-F of the air bag shown in Fig. 14 in another or modified form, in which Fig. 16(a) shows a cross-sectional view prior to deployment in a state in which the air bag is folded up, whereas Fig. 16(b) shows a completely deployed state of the air bag. As shown in Fig. 16(a), the joint portions 81 and 82 are provided in such a manner that there is little sag at a lower surface of a portion constituting a central flow path 84b, and therefore,

when deployed the flow path 84b becomes thinner than flow paths 84a and 84c.

The gas generated from the inflator flows into the three flow paths 84a, 84b and 84c before it flows into a occupant
5 restraint portion.

Fig 17 is a perspective view showing a completely deployed state of an air bag according to another example of the invention in which a joint portion is provided, and Fig. 18 is a cross-sectional view of the air bag 9 shown in
10 Fig. 17 taken along the line G-G thereof. A joint portion 91 can be formed by joining parts of upper and lower panels in a gas flow path portion together in an oval fashion, whereby two flow paths 93a and 93b can be formed in the gas flow path portion.

Fig. 19 is a perspective view showing a completely deployed state of an air bag according to a further example of the invention in which a joint portion is provided in such a manner as to start from an opening portion, and Fig. 20 is a cross-sectional view of the air bag 10 shown in Fig.
15 19 taken along the line H-H thereof. A joint portion 101 can be formed by joining parts of upper and lower panels of a gas flow path portion in such a manner as to form a belt-like configuration extending from the opening portion and having a rounded end, whereby two flow paths 104a and 104b can be
20 formed in the gas flow path portion. In this case, the opening
25

of the air bag is formed into a penetrating configuration which is penetrating into openings 103a and 103b. The gas passes through the openings 103a and 103b and flows into an occupant restraint portion via the flow paths 104a and 104b.

5 In this case, too, however, the number and configuration of gas flow-in portions within a retainer should be made to coincide with those of the openings of the air bag.

Fig. 21 is a perspective view showing a completely deployed state of an air bag according to another example of the invention in which joint portions are provided, Fig. 10 22 is a cross-sectional view of the air bag 11 shown in Fig. 21 taken along the line I-I thereof, and Fig. 23 is a cross-sectional view of the air bag 11 shown in Fig. 21 taken along the line J-J thereof. Joint portions 111, 112 and 113 15 are formed by joining parts of upper and lower panels together at three locations in an air bag deployment direction in a linear fashion. A lower surface of a portion constituting a central flow path 116b is first cut partially away and then is sutured (reference numeral 114 denoting the sutured portion), 20 and therefore the central flow path 116b becomes thinner than flow paths 116a and 116c. The gas passes through the openings 115a, 115b and 115c and then flows into a occupant restraint portion via the three flow paths 116a, 116b and 116c in the gas flow path portion.

25 While there is no limitation to the configurations of

the joint portions, a circular, oval, square, diamond or linear configuration is preferred since they facilitate the formation of the joint portions.

Both the aforesaid penetrating portions and joint portions may be provided in an air bag.

The penetrating portions and/or joint portions are preferably provided in such a manner that the capacity of air bags becomes constant in varying the sizes of air bags as required for different car types, whereby an inflator having a constant output can be used commonly for different car types.

In addition, in a case where an inflator with a constant output is used, the penetrating portions and/or joint portions are preferably provided in such a size that 0.1 to 0.2 second is required from sensing of a collision of the vehicle by the sensor to deflation of the air bag after it is inflated in a front barrier collision test with a test vehicle running speed of 50 to 55km/h.

Preferably a total of cross-sectional areas of penetrating flow paths is 160cm² or greater when portions in a gas flow path portion where the penetrating portions and/or joint portions exist are cut in a plane normal to an air bag deployment direction, and more preferably the total becomes 240cm² or greater. With the total being less than 90cm², not only is the air bag deployed at slower speed but also an internal pressure applied to the gas flow path portion

by the gas becomes so high that there is caused a risk of the air bag being exploded.

Thus, while the air bag system according to the invention has been described heretofore with reference to the appended drawings, the invention is not limited thereto but many modifications can be made thereto without departing from the spirit and scope of the invention.

According to the air bag system of the invention, the capacity of different air bags which are required for different car types can be maintained constant by providing penetrating portions and/or joint portions which are both dimensioned into predetermined sizes. Therefore, the same size inflator can be used commonly on different car types while maintaining the occupant restraining performance of the air bags, whereby the production cost of air bag systems can be reduced. The air bag system of the invention is preferred for use for a front occupant air bag system.

In addition, since the capacity of an air bag can be reduced when compared with a conventional air bag of the same size, an inflator of a smaller output can be adopted, thereby making it possible to make the inflator smaller in size and lighter in weight.